



Ming Feng Lighting Co.,Ltd
 Tel:+86-769-2203-6051 Fax: +86-769-2203-6052
 Add: Wen Tang Administration, East City,Dongguan,Guangdong Province,China.

MF-GP06 Spec

FEATURES

- Light Source: **CREE** CXA2530 COB+ **Bridgelux** surround 5W leds
- Spectrum/Ratio: **Full Spectrum**, Customized Ratio
- Driver: Taiwan **Meanwell LED Drivers**, Wide AC100-265V, PF>0.95
- Waterproof Grade: **IP44**
- Beam Angle: **60°, 90°, 120°**options. Secondary lens 90°
- Lamp Control: Dual switch, CH1: COB; CH2: Surround leds
- Warranty: Design lifespan > 50,000Hrs, **3 years warranty** available.
- Coverage: Vegetative: 3'X4', Flowering: 2'X3'
- Environment: Operation Temperature: -10°C~45°C
Storage Temp.: 0°C~40°C
- Certificated: **CE, TUV, RoHS,CB,SAA, FCC, ETL**



BENEFITS

- Using the latest lighting technology including the USA made CREE COB and Bridgelux 5W leds which are both specifically designed for horticultural lighting.
- Unique secondary Magnifies PAR Lens---much better PAR value and intensity
- 6 channels gardening timing system---built-in timer, 10/12/14/16/18/24 hours for selection
- Application: Vegetable planting, Herbal planting, flower planting, plant factory....etc

SPECIFICATIONS

Product	Model NO:	MF-GP06
	Power :	620W
	Dimension:	554*376*70mm
	Packing:	672*454*160mm/2pcs/carton
	Weight:	N.W: 9.58KG, G.W: 12.5KG
Driver	Input:	AC100-265Vac, 50-60Hz
	PF:	>0.95
	Brand:	Meanwell
LEDS	Color Ratio	Full Spectrum
	Brand:	CREE+ BRIDGELUX
	Numbers:	COB/6PCS, 5W LEDS/96PCS
Coverage	Vegetative:	5'X4'
	Flowering:	4'X4'
Heat management	PCB:	Metal PCB(Aluminum)2.0mm
	Heat conduction:	2.0w/m.k
Environment	Storage Temp.:	0°C~40°C
	Operation Temp.:	-10°C~45°C
Lamp Control	Dual switch, CH1: COB; CH2: Surround leds	
Beam Angle	60°, 90°, 120°options. Secondary lens 90°	
Life span	> 50,000Hrs	

Light Distribution Curve

